SDS—Safety Data Sheet

York Manufacturing, Inc.



| Issue date: June 15, 2015 | Revision date: June 15, 2015 | Version 1 |
|--|----------------------------------|-----------------|
| 1. IDENTIFICATION OF THE SUBST | RATE/PREPARATION AND OF THE COMP | ANY/UNDERTAKING |
| Product identifier | | |
| Product Name Cop-R-Tite Ma | stic | |
| | | |
| Other means of identification | | |
| Product Code MASTIC, MTUE | BES | |
| | | |
| Details of the supplier of the safety data | <u>sheet</u> | |
| Manufacturer Address | | |
| York Manufacturing, Inc. | | |
| 43 Community Drive | | |
| Sanford, ME 04021 | | |
| | | |
| Emergency telephone number | | |
| 8 a.m. to 5 p.m. EST Monday-Friday | 800-551-2828 | |
| Non-Business Hours | 207-651-5738 | |
| 2. HAZARD(S) IDENTIFICTION | | |
| Classification in accordance with pa | ragraph (d) of 29 CFR 1910.1200. | |
| Flammable Liquids - Category 2 | | • |
| Acute Toxicity - Oral - Category 4 | | |
| Skin Corrosion/Irritation - Category 2 | | |

Serious Eye Damage/Eye Irritation - Category 2A

Reproductive Toxicity - Category 1A

Specific Target Organ Toxicity - Single Exposure - Category 1 (respiratory system, central nervous system) Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (kidneys, respiratory system, lungs, central nervous system)

Specific Target Organ Toxicity - Repeated Exposure - Category 2

York Manufacturing Mastic

Precautionary Statement(s)

Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/ vapours/spray Wash thoroughly after handling Do not eat, drink or smoke when using this product

Response

If exposed or concerned: Call a POISON CENTER or doctor/physician IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse Specific treatment (see label)

Storage: Store locked up in a well ventilated and cool area.

Disposal: Dispose contents/container in accordance with local/regional/national/international regulations

Statement of unknown toxicity: Approximately 50% of the mixture is of ingredients of unknown toxicity

Other Hazards: No additional information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| CAS | Component Name | Percent |
|------------|---|---------|
| 14808-60-7 | Quartz | 8-10 |
| 108-88-3 | Toluene | 8-10 |
| 142-82-5 | Heptane (n-) | 15-30 |
| 68410-97-9 | Distillates, petroleum, light distillate hydrotreating process, low-boiling | 15-30 |
| 64742-46-7 | Petroleum distillates, hydrotreated middle | 2-3 |
| 64742-53-6 | Petroleum distillates, hydrotreated light naphthenic | 2-3 |
| 64742-52-5 | Petroleum distillates, hydrotreated heavy naphthenic | 2-3 |

4. First Aid Measures

General advice: If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Eye contact: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact: Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is not required. If skin irritation persists, call a physician.

Inhalation: Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. If symptoms persist, call a physician.

Ingestion: Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. If symptoms persist call a physician. Note to physician this contains asphalt.

York Manufacturing Mastic

Self-protection of the first aider: Use personal protective equipment as required. Most important symptoms and effects, both acute and delayed

Symptoms May cause irritation

Indication of any immediate medical attention and the treatment needed

Note to physicians Treat sympomatically

5. FIREFIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Sand. Alcohol resistant foam. Do not use high pressure water.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Gloves are recommended due to sharp edges.

Enviromental precautions N/A

7. HANDLING AND STORAGE

| Precautions for safe handling | Use personal protective equipment and follow normal jobsite precautions. |
|-------------------------------|--|
| Conditions for safe storage | Keep properly labeled in original packaging, cool , and in a well ventilated area. |
| Incompatibilities_ | Strong acids, bases and strong oxidizing agents. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Component exposure limits:

- Toluene: OSHA 200 ppm TWA, ceiling 300 ppm
- **Quartz:** OSHA only respirable, so this product does not qualify

n-Heptane: OSHA - 500 ppm TWA; 2,000 mg/m³ TWA

Appropriate engineering controls: Provide adequate ventilation and store in a cool area. Ensure compliance with applicable exposure limits.

Personal Protective Equipment (PPE): loves, safety glasses, respirator and protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | green paste | Physical State | liquid |
|--|------------------------|---|---|
| Odor | hydrocarbon odor | Color | green |
| Odor Threshold | Not available | pH | Not available |
| Melting Point | Not available | Boiling Point | 187 °F (86 °C) |
| Freezing point | -90.5 °C | Evaporation Rate | 3.7 |
| Boiling Point Pange | Not available | Flammability (solid_gas) | Not available |
| Boiling Point Range Autoignition Lower Explosive Limit | 433 °F (223 °C) 1 % | Flammability (solid, gas) Flash Point Decomposition | 18 °F (-8 °C) Not available |
| Upper Explosive Limit Vapor Density (air=1) | 7 % Not available | Vapor Pressure Specific Gravity (water=1) | 45 mmHg at 68 ° F (20 °C) Not available |
| Water Solubility | Not available | Partition coefficient: n-octanol/ water | Not available |
| Viscosity | 250000 cps | Solubility (Other) | Not available |
| Density | 6.72 - 7.56 (relative) | VOC | 246.3 g/L |

10. STABILITY AND REACTIVITY

| Reactivity | N/A |
|------------------------------------|----------------------------------|
| Chemical stability | Stable under normal conditions |
| Possibility of hazardous reactions | None under normal conditions |
| Hazardous decomposition products | Oxides of nitrogen and/or carbon |

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| Inhalation | May cause drowsiness, dizziness, respiratory irritation |
|----------------------------------|--|
| Skin contact | Avoid contact with skin |
| Eye contact | Avoid contact with eyes |
| Ingestion | Do not eat this, taste it or put it in your mouth |
| Symptom information | May cause irritation |
| Delayed and immediate effects as | well as chronic effects from short and long term exposure |
| Sensitization | No information available |
| Germ cell mutagenicity | No information available |
| Carcinogenicity | This product does not contain any carcinogens or potential carcinogens as listed by OSHA |

York Manufacturing Mastic

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Asphalt (8052-42-4): Oral LD50 Rat >5000 mg/kg, Dermal LD50 Rabbit >2000 mg/kg

Asphalt, oxidized (64742-93-4): Oral LD50 Rat >5000 mg/kg, Dermal LD50 Rabbit >2000 mg/kg

Distillates, petroleum, petroleum residues vacuum (68955-27-1): Oral LD50 Rat 4320 mg/kg, Dermal LD50 Rabbit >2000 mg/kg

Residues, petroleum, vacuum (64741-56-6): Oral LD50 Rat 4320 mg/kg, Dermal LD50 Rabbit >2000 mg/kg

Hydrogen sulfide (7783-06-4)

Inhalation LC50 Rat 0.99 mg/L 1 h Fatty acids, tall-oil, low-boiling (Mixture): Oral LD50 Rat >2000 mg/kg Dermal LD50 Rat >2000 mg/kg

Component Carcinogenicity:

Petroleum distillates: OHSA: Present

Toluene: OSHA: Present

Styrene-butadiene: not classified

Quartz: OHSA: Present

Additional Data: This product contains silica, but it is not respiratory, since it is bound by the polymer portion of the sealant.

| 12. ECOLOGICAL INFORMA | TION |
|-------------------------------|--------------------------|
| Ecotoxicity | No information available |
| Persistence and degradability | No information available |
| Bioaccumulation | No information available |
| | |

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION

Not a chemical, so no regulatory limitations

16. OTHER INFORMATION

Disclaimer: The information contained on the Safety Data Sheet has been compiled from data considered to be accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. York Manufacturing, Inc.